

KEEP OUT OF REACH OF CHILDREN

DIRECTIONS FOR USE

*Mold & mildew resistance of the dry film coating.

Avoid Freezing.

WRS™-24 concentrate is intended for use on lumber in sawmills and millwork facilities to reduce checking and to improve the surface appearance by reducing extractive bleed. It also allows for more uniform drying of green wood and helps protect dry wood from rewetting.

WRS™-24 concentrate **MUST** only be used with solutions of Bazooka®, Workhorse®, Moldshield® and NP-1® Sapstain Control products and the compatible materials listed below. WRS™-24 concentrate should not be added directly to the treating tank, but must be diluted first in a premix system. WRS™-24 concentrate must be thoroughly agitated before introduction into the premix system. After the ready-to-use preservative solution of Bazooka®, Workhorse® or Moldshield® has been prepared, mix one gallon of WRS™-24 concentrate per 65 to 200 gallons of the preservative solution. Dilution rates will be influenced by seasonal conditions, exposure during storage and transit, treating methods and wood species. If the ready-to-use water repellent preservative solution is not used for 24 hours, this solution should be agitated before use.

Triple rinse any empty drums and add rinsate to the partially filled premix tank; add the balance of water needed.

WRS™-24 concentrate is compatible with Alpha™-8, Timbertreat® ICP-5, Bazooka®, Workhorse®, MoldShield®, NP-1® and NP-2™ Sapstain Control Chemical, Sapstain Control Booster NP-1® Additive, Iron Stain Control Additives, Penetrator™ A20 and Antifoam Additive.

Lumber should be totally immersed or sprayed with the solution to insure all surfaces are treated. In spray applications, adequate spray coverage is critical because less solution is applied to the wood by spraying than by dipping.



Mold & Mildew Resistant* Water Repellent Coating

DILUTE BEFORE USING

*Mold & mildew resistance of the dry film coating

19950

Read Disclaimer on side panel before buying or using. If such terms are not acceptable, return at once unopened.



HAZARDS

Causes severe skin burns and eye damage

May cause an allergic skin reaction

Causes serious eye damage

Harmful if inhaled

May cause genetic defects

Suspected of causing cancer

May damage fertility or the unborn child

Causes damage to organs through prolonged or repeated exposure

Sold By:


Kop-Coat, Inc. dba Kop-Coat Protection Products

3040 William Pitt Way Pittsburgh PA 15238

412-227-2700

Net Contents

Gallons

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Use water spray, fog, Carbon dioxide (CO₂), foam or dry chemical to extinguish fire.

MEDICAL EMERGENCIES: 1-800-222-1222

TRANSPORTATION EMERGENCIES:

Chemtrec 800-424-9300 (US); +1 703-741-5970 (International)

DISCLAIMER

To the extent consistent with applicable law, seller (whether manufacturer, distributor, or other) makes no warranty express or implied, including the implied warranty of merchantability AND IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE regarding this product except the composition as set forth in the ingredient statement herein, and shall not be liable for LOST PROFITS, LOST PRODUCTION, LABOR COSTS, TRANSPORTATION CHARGES, OR ANY special, consequential, INCIDENTAL OR DELAY damages, the exclusive remedy being the replacement of the product. To the extent consistent with applicable law, buyer or user assumes all risk of possession, handling or use of this material when such use and/or handling is contrary to label instructions.